

Thermo Scientific Eutech TN-100 Turbidimeter

Lightweight and waterproof for turbidity measurements

- Lightweight, ergonomic, and waterproof to IP67 – and it floats!
- New design for fast response – full step change in as little as 6 seconds
- Auto range up to 2000 NTU
- Designed to perform over 1,200 tests with most AAA batteries with advanced power management design
- Meets ISO 7027 standards and offers consistent light source for outstanding accuracy
- Three year warranty*

Applications: Ideal for beverage production, drinking water, swimming pools, aquariums, aquaculture and environmental applications



Thermo Scientific™ Eutech™
TN-100 waterproof turbidimeter



Waterproof and Dustproof Housing

IP67-rated waterproof housing allows operation in wet conditions ensuring durability, and easy cleaning and maintenance.

Auto-Ranging from 0 to 2000 NTU

Meter is designed to determine the sample's turbidity level and automatically adjust to the appropriate measurement range.

Sturdy Carrying Case With Accessories

Compact case contains all items necessary for turbidity measurements and protects the meter when not in use. Contents include turbidity meter, four primary calibration standards, three borosilicate sample cuvettes with light shield caps, collection bottle, lint-free cloth, silicone oil, and batteries.

Advanced Power Supply Management

Can measure over 1,200 samples with a single set of batteries, delivering quick, stable results in as little as six seconds. Features auto-off function.

Simple, Display-Prompted Push-Button Calibration

Pressing the "CAL" button initiates the quick and simple calibration procedure. The instrument automatically prompts the user for the next calibration standard.

Large, Easy-to-Read Display

Large, user-customized LCD display shows readings with units of measure and user-friendly message codes that guide meter operation.

Thermo
SCIENTIFIC

* Subject to terms of manufacturer's standard limited warranty.

| Specifications | |
|-----------------------------|---|
| Measuring Parameter | Turbidity |
| Highlights | Light weight, IP67 waterproof meter |
| Principle | Nephelometric non-ratio / ISO 7027 and DIN 27027 compliant |
| Range | 0 to 2000 NTU |
| Automatic Range Selection | 0.01 to 19.99 NTU; 20.0 to 99.9 NTU; 100 to 2000 NTU |
| Resolution | 0.01 NTU (0 to 19.99 NTU); 0.1 NTU (20.0 to 99.9 NTU); 1 NTU (100 to 2000 NTU) |
| Accuracy | < 0.1 NTU for 0.02 NTU standard; $\pm 2\%$ of reading ± 1 digit for 0 to 500 NTU; $\pm 3\%$ of reading ± 1 digit for 501 to 2000 NTU |
| Repeatability | $\leq \pm 1\%$ of reading |
| Calibration | Up to 4 points |
| Calibration Standards | 0.02 NTU, 20.0 NTU, 100 NTU, 800 NTU |
| Response Time | < 6 secs for full step change |
| Sample Volume | 10 mL |
| Light Source | Infrared-emitting diode (850 nm wavelength) |
| Operating Temperature Range | 0 to 50 °C |
| Sample Temperature Range | 0 to 50 °C |
| Enclosure Type & Rating | ABS plastic & IP67 rated |
| Power | 4 x 1.5 V 'AAA' alkaline batteries (> 1200 readings) |
| Certifications/Compliance | FCC part 15 class A, TUV 3 in 1, CE, RoHS |
| Dimensions (LxWxH) | Meter: 15.5 x 6.8 x 4.6 cm; Boxed: 35.5 x 16.5 x 10.5 cm |
| Weight | Meter: 200 g; Boxed: 1,160 g |

| Ordering Information | |
|----------------------|--|
| Order Code | Description |
| ECTN100IR | Waterproof TN-100 handheld turbidimeter with set of 4 calibration standards (800, 100, 20.0 & 0.02 NTU), set of 7 sample vials, lint-free cloth, silicone oil, batteries, and hard carrying case |
| ECTN100NOSTDS | Waterproof TN-100 handheld turbidimeter, set of 7 sample vials, lint-free cloth, silicone oil, batteries, and hard carrying case |
| TN100CALKIT | Calibration kit set – standard solutions (0.02, 20.0, 100, 800 NTU) 60 mL each and (4) vials |
| ECTN100CUVKIT | Pack of 3 cuvettes (vials) |
| ECTN100CUVKIT4 | Pack of 4 cuvettes (vials) |
| ECSILICONEOIL | Silicone oil (10 mL) |
| 32X366401 | Replacement light shield cover |
| 67X357201 | Replacement cloth |



60 mL bottles of US EPA-approved
non-formazin standards
– stable and easy to use



Index markings on the cuvettes
make it easy to perform
repeatable measurements


eutechinst.com

© 2015 Thermo Fisher Scientific Inc. All rights reserved. All trademarks are the property of Thermo Fisher Scientific and its subsidiaries.

Water and Lab Products

North America

Toll Free: 1-800-225-1480
Tel: 1-978-232-6000
info.water@thermofisher.com

Germany

Tel: (49) 6184-90-6000
info.water.uk@thermofisher.com

China

Tel: (86) 21-68654588
wai.asia@thermofisher.com

India

Tel: (91) 22-4157-8800
wai.asia@thermofisher.com

Singapore

Tel: (65) 6778-6876
wai.asia@thermofisher.com

Japan

Tel: (81) 045-453-9175
wai.asia@thermofisher.com

Australia

Tel: (613) 9757-4300
In Australia: (1300) 735-295
InfoWaterAU@thermofisher.com

Thermo
SCIENTIFIC

A Thermo Fisher Scientific Brand